

SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

Revision date: 11/7/2023 Version: 1.4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Trade name:	SkamoAlu Sical 78 Mortar		
1.2. Relevant identified u	ses of the substance or mixture and uses advised against		
Recommended uses:	Mortar. Please see technical data sheets for further specifications.		
1.3. Details of the supplie	er of the safety data sheet		
Supplier			
Company:	Skamol Group		
Address:	Hasselager Centervej 1		
Zip code:	8260		
City:	Viby J		
Country:	DENMARK		
E-mail:	info@skamol.com		
	+45 97 72 15 33		
1.4. Emergency Telephor +45 97 72 15 33 (Skamol Gro	ne Number up)		
Phone: 1.4. Emergency Telepho +45 97 72 15 33 (Skamol Gro SECTION 2: Hazards ic	ne Number up)		
1.4. Emergency Telephor +45 97 72 15 33 (Skamol Gro	ne Number up) Ientification		
1.4. Emergency Telephon +45 97 72 15 33 (Skamol Gro SECTION 2: Hazards io	ne Number up) Ientification		
1.4. Emergency Telephon +45 97 72 15 33 (Skamol Gro SECTION 2: Hazards in 2.1. Classification of the	The product shall not be classified as hazardous according to the classification and labeling rules for substance and mixtures.		
1.4. Emergency Telephon +45 97 72 15 33 (Skamol Gro SECTION 2: Hazards in 2.1. Classification of the CLP-classification: Most serious harmful effect	ne Number nup) Ientification substance or mixture The product shall not be classified as hazardous according to the classification and labeling rules for substance and mixtures. s: May cause slight irritation to the skin and eyes. Handling of the product causes risk of dust		
1.4. Emergency Telephon +45 97 72 15 33 (Skamol Gro SECTION 2: Hazards in 2.1. Classification of the CLP-classification:	ne Number nup) dentification substance or mixture The product shall not be classified as hazardous according to the classification and labeling rules for substance and mixtures. s: May cause slight irritation to the skin and eyes. Handling of the product causes risk of dust formation, which may irritate nose and throat.		

2.3. Other hazards

The product does not contain any PBT or vPvB substances. Endocrine disrupting properties: None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No./ EC No./ REACH Reg. No.	Concentration	Notes	CLP-classification
Kaolin / Clay	1332-58-7 310-127-6	< 10 %		STOT RE 2;H373
Sodium silicate	1344-09-8 215-687-4 01-2119448725-31	< 7 %		Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335

Please see section 16 for the full text of H- / EUH-phrases.



SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

Revision date: 11/7/2023 Version: 1.4.0

SECTION 4: First aid measures

4.1. Description of first aid measu	res
-------------------------------------	-----

Inhalation:	Seek fresh air, wash out mouth with water and blow nose thoroughly.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.
Skin contact:	Remove contaminated clothing. Wash the skin with water.
Eye contact:	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
General:	When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

May cause slight irritation to the skin and eyes. Inhalation of dust may cause irritation to the upper airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.

Unsuitable extinguishing Do not use water stream, as it may spread the fire. **media:**

5.2. Special hazards arising from the substance or mixture

Can generate harmful flue gases containing carbon monoxide in the event of fire.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with chemical resistant gloves.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Wear safety goggles if there is a risk of dust contact with eyes.

For emergency responders: In addition to the above: Normal protective clothing equivalent to EN 469 is recommended.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water.

6.3. Methods and material for containment and cleaning up

Sweep up/collect spills for possible reuse or transfer to suitable waste containers. Wipe up minor spills with a damp cloth.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage



SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

7.1. Precautions for safe handling

Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

The product should be stored safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Store in a dry area.

7.3. Specific end use(s)

No special uses in addition to identified uses in 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit

Occupational	exposure limit						
Substance name	Time period	ppm	mg/m³	fiber/cm3	Remarks	Notation	
Quartz	8h		0.1		Respirable fraction. OEL value for: Silica, crystalline		
Measuring methods:		Compliance with occupational exposure limits may be checked by occupational hygiene measurements.					
Legal basis:	- (t		Commission Directive 2000/39/EC (Occupational Exposure Limits) as subsequently amended. Last amended by Commission Directive 2019/1831/EU. Directive 2004/37/EC (Exposure to carcinogens or mutagens at work) as subsequently amended. Last amended by Directive 2022/431/EU. Resolution 2019/2182(INL) (Protecting workers from asbestos) as subsequently amended. Last amended by resolution 2022/C 184/03.				
8.2. Exposure	controls						
Appropriate engineering controls:		Wear the personal protective equipment specified below.					
Personal protective equipment, eye/face protection:		Wear safety goggles if there is a risk of dust contact with eyes. Eye protection must conform to EN 166.					
Personal protection		ent, Plastic or rubber gloves recommended.					
Personal protect respiratory pro		t, Wear respiratory protective equipment with P2 filter when performing dusty work. Respiratory protection must conform to one of the following standards: EN 136/140/					
Environmental controls:	exposure	Ensure compliance with local regulations for emissions.					

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Solid substance / Powder
Colour	Grey
Odour	No data
Solubility	Partly soluble

Revision date: 11/7/2023

Version: 1.4.0



SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

Revision date: 11/7/2023 Version: 1.4.0

Parameter	Value/unit	Remarks
Odour threshold	No data	
Melting point	1700 °C	
Freezing point	No data	
Initial boiling point and boiling range	No data	
Flammability (solid, gas)	No data	
Flammability limits	No data	
Explosion limits	No data	
Flash Point	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
pH (solution for use)	12	
pH (concentrate)	No data	
Kinematic viscosity	No data	
Viscosity	No data	
Partition coefficient n-octonol/water	No data	
Vapour pressure	No data	
Density	No data	
Relative density	No data	
Vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

9.2. Other information

Bulk density: 2,5 g/ml

SECTION 10: Stability and reactivity

10.1. Reactivity

Other Information:

Not reactive.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

Dust may form explosive mixtures with air.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information



SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

Revision date: 11/7/2023 Version: 1.4.0

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral:	Ingestion may cause discomfort. The product does not have to be classified. Test data are not available.		
Acute toxicity - dermal:	The product does not have to be classified. Test data are not available.		
Acute toxicity - inhalation:	The product does not have to be classified. Test data are not available.		
Skin corrosion/irritation:	May cause slight irritation. The product does not have to be classified. Test data are not available.		
Serious eye damage/eye irritation:	Temporary irritation. The product does not have to be classified. Test data are not available.		
Respiratory sensitisation or skin sensitisation:	The product does not have to be classified. Test data are not available.		
Germ cell mutagenicity:	The product does not have to be classified. Test data are not available.		
Carcinogenic properties:	The product does not have to be classified. Test data are not available.		
Reproductive toxicity:	The product does not have to be classified. Test data are not available.		
Single STOT exposure:	Inhalation of dust may cause irritation to the upper airways. The product does not have to be classified. Test data are not available.		
Repeated STOT exposure:	The product does not have to be classified. Test data are not available.		
Aspiration hazard:	The product does not have to be classified. Test data are not available.		
11.2. Information on other hazards			
Endocrine disrupting properties:	None known.		
Other toxicological effects:	None known.		

SECTION 12: Ecological information

12.1. Toxicity

The product does not have to be classified. Test data are not available.

12.2. Persistence and degradability

Test data are not available.

12.3. Bioaccumulative potential

Test data are not available.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

None known.



SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Avoid discharge to drain or surface water. If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste (Dir. 2008/98/EU). Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

Empty, cleansed packaging should be disposed of for recycling. Uncleansed packaging is to be disposed of via the local wasteremoval scheme.

Category of waste:Product: 16 05 09 discarded chemicals other than those mentioned in 16 05 06, 16 05 07
or 16 05 08

Absorbent/cloth contaminated with the product: EWC code: 15 02 03 Absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02.

SECTION 14: Transport information

14.1. UN number or ID number:	Not applicable.
14.2. UN proper shipping	Not applicable.
name:	
14.3. Transport hazard class(es):	Not applicable.

14.4. Packing group: 14.5. Environmental hazards: Not applicable. Not applicable.

14.6. Special precautions for user

None.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: None.

15.2. Chemical Safety Assessment

REACH Reg. No.	Substance name
01-2119448725-31	Sodium silicate

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.4.0	11/7/2023	Bureau Veritas HSE/SUJ	7,8,16

Abbreviations:	PBT: Persistent, Bioaccumulative and Toxic vPvB: Very Persistent and Very Bioaccumulative STOT: Specific Target Organ Toxicity	
Other Information:	This safety data sheet has been prepared for and applies to this product only. It is based of our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on	n

Revision date: 11/7/2023 Version: 1.4.0



SkamoAlu Sical 78 Mortar

Replaces date: 1/2/2023

Version: 1.4.0 preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

Revision date: 11/7/2023

Training advice:A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method: Calculation based on the hazards of the known components.

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Supplemental hazard information

EUH210 Safety data sheet available on request.

SDS is prepared by

Company:	Bureau Veritas HSE Denmark A/S
Address:	Oldenborggade 25-31
Zip code:	7000
City:	Fredericia
Country:	DENMARK
E-mail:	infohse@bureauveritas.com
Phone:	+45 77 31 10 00
Homepage:	www.bureauveritas.dk

Country:

EU