

Declaration of Performance




No. DoP672010

- Product type:**
General purpose mortar (GP)
- Constructions product identification:**
SkamoWall Smooth Plaster
- Intended use of construction product:**
Intended for use on walls, ceilings and partitions, in particular as mineral filler used for silicate-limestone panel
- The manufacturer's name and address:**
Skamol A/S
Østergade 58-60
DK-7900 Nykøbing Mors
- The authorized representative's name and address:**
Not relevant
- Systems of assessment and verification of constancy of the performance (AVCP):**
AVCP-System 4
- Notified body tasks, if relevant:**
Not relevant
- Declared performance:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	EN 998-1:2010, IDT
Dry bulk density [kg/m ³]	≤1400	EN 998-1:2010, IDT
Compressive strength	CS II	EN 998-1:2010, IDT
Water absorption	Class W0	EN 998-1:2010, IDT
Water vapor permeability, μ	≤15	EN 998-1:2010, IDT
Adhesion	≥ 0,08 N/mm ² Fracture pattern B	EN 998-1:2010, IDT
Thermal conductivity, λ _{10,dry}	≤ 0.45 W/mK (average tabular value, P=50%)	EN 998-1:2010, IDT
Dangerous substances	See safety data sheet	EN 998-1:2010, IDT

- The performance of the construction product referred to in point 1 and 2, are consistent with the declared performance in point 8.**
This declaration of performance is issued under the regulation (EU) No.305/2011 and under the sole responsibility of the manufacturer, listed in point 4. Signed for and on behalf of the production by:



Susanna Knudsen, Quality Manager, Skamol A/S

Nykøbing Mors 11-09-2017, rev 02

Skamol

Østergade 58-60, 7900 Nykøbing Mors, Denmark

Tel.: +45 97 72 15 33

www.skamol.com

